

21B Series – Specifications

Case – Machined from solid extruded brass.

Standard finish is 626 satin chromium plated.

Width – 1 25/32”

Length – 2 1/16”

Thickness – 13/16”

Shackle – The shackle locks at both heel and toe. The length of shackle opening is measured from top of case to inside of shackle when padlock is locked.

Material – Stainless steel

Diameter – 5/16”

Width of opening – 7/8”

ASTM F883 – Meets Grade 4 with stainless steel shackle.

ASTM F883 – Meets Grade 6 for shackle cutting force with XSPL shackle option.

ASTM F883 – Meets Grade 6 for option E. (Corrosion resistance).



21B Padlock



21B72

21B722

21B772

21B782

21B – How to Order

21B	7	2	T			
Series	Core Housing	Shackle Height	Function Code	Chain Option	Special Stamp No.	Options
21B – brass 5/16” dia.	7 – 7 pin housing accepts all BEST® cores	Steel 2 – 3/4” 21 – 1” w/shroud 22 – 1 1/2” 72 – 2” 82 – 4” Brass 0 – 3/4” 20 – 1 1/2” 70 – 2” 80 – 4”	T – key retained L – non-key retained	M – case drilled for clevis only M1 – bronze chain M5 – galvanize steel chain with grey polycoating	Blank –BEST® logo PS1010 –safety first Specify padlock stamp number or describe stamp. Price for special stamps on request.	606 – satin brass SH – shrouded with cut resistant shackle WC – weather cover XSPL – cut resistant shackle
				page 8	page 8	page 6–9